

**HYPER 4300**



**Standard equipment:**

- 
  - 2 x 5.511.1168  
PPL brush Ø 360 mm - 14"
- 
  - 4.508.0646  
Front squeegee blade L.925 mm  
Shore 40 Th. 3 mm
  - 4.508.0605  
Rear squeegee blade L.1015 mm  
Shore 30 Th. 4 mm
- 
  - 0.108.0049  
Battery Charger 24V 25A  
220-240/50-60

- Capable to work for the maintenance and deep cleaning of large areas (up to 2.600 m<sup>2</sup>)
- User friendly control panel: forward speed setting, scrubbing and vacuuming selectors, battery charge indicator, traction direction indicator, key main switch
- Large handle with traction driving lever for forward and backward directions
- Self levelling brush plate
- Cover removable without tools
- Quick vacuum motor and filter inspection, without tools
- Detergent solution filter
- Detergent solution tank provided with large opening protected by quick locking cap.
- Battery charger included

	HYPER 4300
code	8.517.0111
power supply	24V (battery charger included)
scrubbing / squeegee width	750 / 900 mm
max working capacity	4275 m <sup>2</sup> /h
detergent tank capacity	88 l / 23.25 gal
recovery tank capacity	91-95 l / 24.04-25 gal
traction type / power	automatic / 300 W
RPM - pressure on the brushes	150 - 48,5 kg / 107.48 lbs
brush motor power	1000 W
detergent solution system	solenoid valve
depression / vacuum motor	1733 mmH <sub>2</sub> O / 550 W
dimensions / weight	133x73x117 cm / 153 kg



Easy access to battery and vacuum motor compartment, without using tools. Large capacity shock and acid proof polyethylene tanks (88 l) avoid frequent refilling and idle time. 4 x 6V -180 Ah C5 batteries granting continuous working time up to 4-5 hours.

Adjustable speed ensures high precision in cleaning congested areas with obstacles. Intuitive controls reduce operator's training time. Safety thermal breakers prevent motor problems in case of overheating or operator's misuse.



Heavy duty V-shaped squeegee ensures perfect drying of every type of floor, even with large joints. Non-marking wheels avoid marks after the drying. Completely adjustable to fit any surface.

Strong mechanical control levers for heavy duty use. Large size drain hose for a fast emptying and a better cleaning of the recovery tank. Quick fitting battery charger plug.



### Optional accessories:



- 4 x 0.107.0004  
Tubular battery Pb-acid  
6V 180Ah C5



- 4 x 0.107.0072  
GEL Battery 6 MFP 180  
6V 180Ah C5



- 0.108.0002  
Battery Charger 24V 25A  
220-240/50-60



- 4.508.0901 Polyurethane  
front blade L.925 TH.3 Sh.40
- 4.508.0900 Polyurethane  
rear blade L.1015 TH.4 Sh.40



- 5.511.1246  
Tynex brush Ø 360 mm-14"

- 5.511.1169  
PPL 0,03 brush Ø 360 mm-14"

- 5.511.1203  
PES brush Ø 360 mm - 14"



- 5.511.1129  
EWU pad driver Ø 360 mm-14"



(5 pcs package)

- 6.508.0143 - Ø 380 mm-15" - beige
- 6.508.0144 - Ø 380 mm-15" - green
- 6.508.0141 - Ø 380 mm-15" - black