

hospitals, bars, gyms, restaurants • Adjustable flow (automatic start-stop with solenoid valve) of the detergent solution

depending on type of surface

• Brush with quick release

• Removable recovery tank

• Available in battery version (on request) with integrated battery charger with data

- memory and for any type of batteries
- Battery included
- Squeegee lifting lever
- Compact reclining handle with control switches
- Easy access and simple service of the components.


	FLEXI 1250 E
code	8.518.0055
power supply	220/240 V - 50/60 Hz
scrubbing / squeegee width	360 / 460 mm
max working capacity	1260 m²/h
detergent tank capacity	11   / 2.91 gal
recovery tank capacity	12-13   / 3.2 gal
traction	mechanical
RPM / pressure on the brushes	130/18 kg /40 lbs
brush motor power	370 W
detergent solution system	solenoid valve
depression / vacuum motor	850 mmH <sub>2</sub> O/400 W
dimensions / weight	120x43x97 cm / 49kg





The unit can be supplied mains (15 m cable available) or battery powered. Reclining handle: fit on any operator's height and allowing the perfect cleaning also on 90° corners. Shock-absorbing covers, simple cleaning of the recovery tank, non marking wheels.

Easy access to mechanical parts ( easy maintenance of each component ), removable recovery tank without tools.






User friendly analogic control panel. Control lever for brush operation and detergent water outflow.

General ON/OFF switch, brush and vacuum motor switch, solenoid valve operation switch.

Parabolic squeegee, easy rubber blades replacement. The floating brush plate and squeegee grant the right cleaning pressure on any type of floor.



## **Optional accessories:**



• 4.508.1100 Polyurethane front blade L.537 TH. 1,5 • 4.508.1101 Polyurethane rear blade L.590 TH. 2,5



5.511.1413
Tynex brush Ø 360 mm-14"
5.511.1411
PPL 0,03 brush Ø 360 mm-14"
5.511.1412
PES brush Ø 360 mm-14"



• 5.511.1129 EWU pad driver Ø 360mm-14"

