

### NPX XP



#### Standard equipment:

- 3.700.0036 Gun M22 - 3/8" (mod 1211 XP-1511 XP).



- 3.700.0030 Gun M22 - 3/8" with rotating coupling (mod. 1813 XP).



- 3.701.0015 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 045 (mod. 1211 XP)
- 3.103.0049 Nozzle type 040 (mod. 1511 XP)
- 3.103.0049 Nozzle type 040 (mod. 1813 XP)



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m

#### Optional:

- cod.6.608.0019 Hose-reel with brake (hose not included)

**VERSION**  
**60**  
**Hz**  
**AVAILABLE**  
**DETAILS PAGE 33**

#### Equipped with:

- Three ceramic coated pistons, brass axial pump head with built-in by-pass valve. • Low voltage and delayed Total Stop. • Suction and delivery S/S valves. • Vertical burner with high thermal efficiency steel coil. • Temperature regulation gauge. • Low fuel lamp. • Safety valve.
- Detergent built-in tank for indirect suction. • Pressure regulator. • Glycerine pressure gauge.
- Panel with analogic controls. • Heavy duty steel frame. • Accessory holder. • Two ways fuel pump. • Hose-reel with brake (**optional**)

	NPX 1211 XP	NPX 1511 XP	NPX 1813 XP
code	8.620.0601	8.620.0602	8.620.0617
operat. pressure/max	120/150 bar-11450/2175 psi	150 bar-2175 psi	180 bar-2610 psi
delivery rate	660 l/h-2.91 GPM	660 l/h-2.91 GPM	780 l/h-3.43 GPM
abs. power/voltage	3200W - 230V~50Hz 1ph	4000W - 400V~50Hz 3 ph	6300W - 400V~50Hz 3 ph
motorpump type/RPM	MPBX2/2800 RPM	MPBX2/2800 RPM	MPBX2/2800 RPM
max. temp. inlet/outlet	40/140 °C	40/140 °C	40/140 °C