

## Thermic 10 HW Hot water self-contained unit



**T.V.** Thermal Valve



### Standard equipment:

- 6.601.0001 Gun PRO S'10 3/8 M with quick connection



- 6.602.0044 Lance 900 mm with quick connection.



- 3.103.0052 Nozzle type 055



- 4.618.0012 High pressure hose 10 m



### Optional:

- S/S header tank (high pressure chemical)
- Varnished soundproofing steel cover set code 6.608.0014
- Trolley set with inflateable wheels & handles code 6.608.0020



### Equipped with:

- Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- By-pass thermal protection with safety valve.
- Electrical start with full engine functions control.
- Auxiliary belt driven sturdy alternator.
- Lombardini diesel engine 15LD400 (air cooled).
- Pump-motor gearbox (1.650 rpm).
- Automatic engine RPM regulator.
- Integrated detergent suction with external suction probe.
- Electrical start with engine functions control.
- Unique diesel tank for engine and burner.
- Battery included.

Thermic 10 HW	
code	8.601.0099
operat. pressure	170 bar-2465 psi
delivery rate	1020 l/h-4.49 GPM
engine type/hp	Lombardini 15LD400/10
pump type/RPM	CL5/1650 RPM
max. temp. inlet/outlet	40/140 °C