

**HYPER 2000 E**



**Standard equipment:**

- 5.511.1097  
PPL brush Ø 483 mm - 19"

---

- 4.508.X468  
Front squeegee blade L.830 mm Shore 40 Th. 2.5 mm
- 4.508.X467  
Rear squeegee blade L.870 mm Shore 40 Th. 3 mm

- Very compact scrubbing machines suitable to work for the maintenance cleaning of limited-size areas (up to 1.500 m<sup>2</sup>)
- Especially suitable for cleaning: car shops, sales points, gym, health care
- Control panel with operator presence safety system
- Low level battery indicator: brush/vacuum and traction progressive cut off
- Solution water filter and solenoid valve
- Easy access to the battery compartment
- Quick drain and easily inspectable recovery tank
- Non-marking wheels
- Roto-molded polyethylene tanks, shock and acid resistant
- The lower tank also serves as battery compartment
- Low noise operation thanks to the protected positioning of vacuum motor.

HYPER 2000 E	
code	8.527.0038
power supply	230V
scrubbing / squeegee width	500 / 800 mm
max working capacity	2000 m <sup>2</sup> /h
detergent tank capacity	44 l / 11,63 gal
recovery tank capacity	50-60 l / 13,21-16 gal
traction	mechanical
RPM / pressure on the brushes	150/20 kg / 44,09 lbs
brush motor power	550W
detergent solution system	solenoid valve
depression / vacuum motor	1700 mmH <sub>2</sub> O/1000W
dimensions / weight	116x46x98cm / 95 kg



Powerful gearmotor; metal brush plate with integrated plastic splash guard/bumper.

### Optional accessories:



- 4.508.1178 Polyurethane front blade L.830 TH. 3
- 4.508.1177 Polyurethane rear blade L.870 TH. 4



- 5.511.1098 Tynex brush Ø 483 mm-19"
- 5.511.1128 PPL 0,03 brush Ø 483 mm-19"
- 5.511.1206 PES brush Ø 483 mm - 19"



- 5.511.1099 EWU pad driver Ø 483 mm-19"



- 6.508.0034 Abrasive pad Ø 483 mm-19" - beige (5 pcs.)
- 6.508.0041 Abrasive pad Ø 483 mm-19" - green (5 pcs.)
- 6.508.0048 Abrasive pad Ø 483 mm-19" - black (5 pcs.)



- 4.512.0068 Extension electric cord 15 m with Schuko plug

The outflow of the detergent solution is controlled by a solenoid valve. The actuation of the solenoid valve is operated by the control lever, avoiding the detergent solution outflow when the brush is stopped during the interruptions of work.



Renovated squeegee with new pressure adjusting system. The squeegee blades are easily replaceable without the use of tools. Quick and easy squeegee coupling through the two large knobs; the squeegee is released without any damage in the event of accidental impact.

Easy and intuitive controls. The outflow of the cleaning solution is easily controlled using the mechanical lever placed on the control panel. Inspectable mesh filter to trap any existing solid body in the cleaning solution.

