

## Hyper 1600 E



### Standard equipment:



- 5.511.1941 PP brush Ø 430 mm - 17"



- 4.508.1319 Front squeegee blade Shore 40 Th. 2,5 mm
- 4.508.1320 Rear squeegee blade Shore 40 Th. 3,0 mm

- Ideal for small and medium floors up to 1600sqm, especially when congested by people or furnishing like in wellness centres, gyms, car showroom, retail shops, hospitals and schools.
- Automatic brush attachment, discharge and delayed cut-off.
- Adjustable solution release with automatic cut-off.
- Narrow body with both side brush protrusion and 300° squeegee spin.
- Tool less removable recovery tank with large visual inspection window and stretchable discharge hose.
- Adjustable driving handle with dead man switches, soft touch controls and diagnosis (Eco Energy mode and battery low level automatic cut-off for DC version).
- Large non marking working wheels and sturdy rear roller for displacements.



Watch the video on youtube:  
[www.youtube.com/lavorpro](http://www.youtube.com/lavorpro)

### Hyper 1600E

code	8.580.0022
power supply	230V 50Hz
scrubbing/squeegee width	450/540 mm
max working capacity	1600 m <sup>2</sup> /h
solution tank capacity	30 l/7.92 gal
recovery tank capacity	32-35 l/8.45 - 9.24 gal
traction	mechanical
RPM/pressure on the brushes	150/18 kg/39,68 lbs
brush motor power	300 W
detergent solution system	solenoid valve
depression/vacuum motor	1200 mmH <sub>2</sub> O/800 W
dimensions/weight	117x58x78 cm/66 kg