



## GV 3,3 M plus


### Standard equipment:

- 5.409.0256 Hose 3 m 

---

- 3.753.0111 

---

- 3.754.0228 


---

- 3.754.0229 

---

- 3.754.0235 


---

- 3.754.0250 

---

- 3.754.0230 


---

- 6.405.0207 


---

- 6.402.0096 

---

- 3.754.0234 

---

- 6.402.0095 

---

- 3.099.0126 



### Equipped with:

- Saturated steam at 9 bar at a temperature of 175°C • Steam gun with low tension control • Made of AISI 304 stainless steel • Boiler 3,3 kW S/S AISI 304. Thickness 25/10 • Heating and activation time required: 7 min. • Steam regulation
- Discharge valve • Pressure gauge • Device for using chemicals and detergents mixed with steam • The boiler can be refilled from the tank provided (continuous duty)
- Pivoting wheels with brakes, suitable for use in food processing areas.

GV 3,3 M PLUS	
Code	8.450.0010
Max steam pressure/temperature	9 bar / 175° C
Boiler absorbed power	3.3 kW / 230V ~ 50Hz (Ph 1)
Steam production	4.62 kg/h
Boiler type/volume	Inox AISI 304 / 4 l
Water tank/detergent tank capacity	5 l / 5 l